

# EnviroGrip Primer

Primer for CONPELL EnviroGrip textured coating

## DESCRIPTION

CONPELL EnviroGrip primer is a specifically formulated primer for use with CONPELL Envirogrip and CONPELL Envirogrip RC.

## PRODUCT FEATURES & BENEFITS

- Cost effective
- Highly liquid
- High bond strength
- Fast drying
- Australian made

## TYPICAL APPLICATIONS

Used as a primer for the CONPELL EnviroGrip and Envirogrip RC product range.

## TOTAL VOC

TVOC's calculated as the sum total of the VOC's of each individual raw material component. The total VOC is <10 grams/ litre of ready to use product.

## PACKAGING

CONPELL EnviroGrip primer is available in 5ltr and 1ltr containers.

## COVERAGE

1 litre of CONPELL EnviroGrip primer diluted with 9 litres of clean water will cover 60 – 80m<sup>2</sup>, depending on the porosity of the substrate.

## SURFACE PREPARATION

All concrete surfaces should be structurally sound and free of all contaminating material, including all previous coatings, adhesives, dirt, grease, oil, waxes, efflorescence or laitance by abrasive mechanical grinding.

## PRIMER APPLICATION

Apply the diluted primer evenly using a brush and roller, allow to become tacky or dry, before the application of CONPELL EnviroGrip or Envirogrip RC. Envirogrip or Envirogrip RC must be applied within 12 hours of primer application, if more than 12 hours has passed the surface should be re-primed.

Extremely porous substrates may require a second coat of primer. If a second coat of primer is required allow the first coat to dry prior to application of the second coat.

## DO NOT APPLY CONPELL ENVIROGRIP TO UNPRIMED SURFACES

Do not allow dust or dirt to cover the primed substrate, if this occurs the area must be re-primed prior to the application of CONPELL EnviroGrip or Envirogrip RC. For concrete substrates subject to rising damp or moisture, a waterproof membrane is required. It is recommended that CONPELL Vapour Shield be used as the primer.

# EnviroGrip Primer

Primer for CONPELL EnviroGrip textured coating

## MIXING

CONPELL EnviroGrip primer is supplied as a concentrate and requires mixing with water at a ratio of 9 parts clean water to 1 part CONPELL EnviroGrip primer. DO NOT OVER DILUTE.

## CLEAN UP

Clean all material with water.

## STORAGE

Keep CONPELL EnviroGrip primer stored in a dry area, away from direct sunlight & frost, Store between 10°C & 30°C. CONPELL EnviroGrip primer has a shelf life of 12 months in an unopened drum.

## FIRE

**Product is non-flammable and poses no fire risk.**

## SAFETY PRECAUTIONS

- Wear appropriate protective equipment including clothing, gloves, appropriate respiratory mask and goggles.
- If poisoning occurs, contact doctor or Poisons Information Centre.
- If contact with skin occurs, remove contaminated clothing and thoroughly wash skin.
- If swallowed do not induce vomiting, give a glass of water.
- If in eyes, hold eyes open and flood with water for at least 15 minutes then see doctor immediately.
- For further information refer to the relevant Material Safety Data Sheet.

## IMPORTANT INFORMATION

The information and recommendations relating to EnviroGrip Primer are given based on current knowledge and experience. Due to variances in material substrates and site conditions no warranties implied by law or, fit to purpose of the product can be implied. We accept no responsibility for loss or injury due to the incorrect handling or improper use of the product, limiting the cost of our liability to the replacement product cost only. Always refer to current Product Technical Data Sheets.

## CONPELL

Head Office: PO Box 4252  
Loganholme DC, Qld 4129

Ph: 1300 966 118

Brisbane Sales: 0450 040 848

National Sales: 0433 400 220

Email: [info@conpell.com](mailto:info@conpell.com) Web: [www.conpell.com](http://www.conpell.com)