

EnviroGrip Primer

High performance primer for CONPELL EnviroGrip textured coating

DESCRIPTION

CONPELL EnviroGrip primer is a specifically formulated primer for use with CONPELL Envirogrip.

PRODUCT FEATURES & BENEFITS

- Cost effective
- Highly liquid
- High bond strength
- Fast drying
- Australian made

TYPICAL APPLICATIONS

Used as a primer for CONPELL EnviroGrip product.

VOC RATING

TESTED UNDER THE REQUIREMENTS OF:

IEQ 13 VOLATILE ORGANIC COMPOUNDS "GREEN STAR TECHNICAL MANUAL"

TVOC's calculated as the sum total of the VOC's of each individual raw material component.

The total VOC is <10 grams/ litre of ready to use product.

PACKAGING

CONPELL EnviroGrip primer is available in 1ltr containers.

COVERAGE

1 litre of CONPELL EnviroGrip primer diluted with 9 litres of water will cover 60 – 80m² per litre, depending on the porosity of the substrate.

SURFACE PREPARATION

All concrete surfaces should be structurally sound and free of all contaminating material, including all previous coatings, adhesives, dirt, grease, oil, waxes, efflorescence or laitance by abrasive blasting, high pressure water blasting, scarifying, mechanical scrubbing or other means.

EnviroGrip Primer

High performance primer for CONPELL EnviroGrip textured coating

PRIMER APPLICATION

Apply the diluted primer evenly using a brush, roller or broom and allow to become tacky, before the application of CONPELL EnviroGrip.

Extremely porous substrates may require a second coat of primer. If a second coat of primer is required allow the first coat to dry prior to application of the second coat.

DO NOT APPLY CONPELL ENVIROGRIP TO UNPRIMED SURFACES

Do not allow dust or dirt to cover the primed substrate, if this occurs the area must be re-primed prior to the application of CONPELL EnviroGrip. For concrete substrates subject to rising damp or moisture, a waterproof membrane is required. It is recommended that CONPELL Vapour Shield be used as the primer.

MIXING

CONPELL EnviroGrip primer is supplied as a concentrate and requires mixing with water at a ratio of 9 parts water to 1 part CONPELL EnviroGrip primer. DO NOT OVER DILUTE.

CLEAN UP

Clean all material with water.

STORAGE

Keep CONPELL EnviroGrip primer stored in a dry area, away from direct sunlight & frost, Store between 10°C & 30°C. CONPELL EnviroGrip primer has a shelf life of 12 months in an unopened drum.

FIRE

Product is non-flammable and poses no fire risk.

SAFETY PRECAUTIONS

- Wear appropriate protective equipment including clothing, gloves, appropriate respiratory mask and goggles.
- If poisoning occurs, contact doctor or Poisons Information Centre.
- If contact with skin occurs, remove contaminated clothing and thoroughly wash skin.
- If swallowed do not induce vomiting, give a glass of water.
- If in eyes, hold eyes open and flood with water for at least 15 minutes then see doctor immediately.
- For further information refer to the relevant Material Safety Data Sheet.

EnviroGrip Primer

High performance primer for CONPELL EnviroGrip textured coating

IMPORTANT INFORMATION

The information and recommendations relating to EnviroGrip Primer are given based on current knowledge and experience. Due to variances in material substrates and site conditions no warranties implied by law or fit to purpose of the product can be implied. We accept no responsibility for loss or injury due to the incorrect handling or improper use of the product, limiting the cost of our liability to the replacement product cost only. Always refer to current Product Technical Data Sheets.

CONPELL

Head Office: PO Box 4252

Ph: 1300 966 118

Brisbane Sales: 0450 040 848

Loganholme DC, Qld 4129

Fax: 1300 922 001

National Sales: 0433 400 220

Email: info@conpell.com Web: www.conpell.com