

Envirotop W

Spray or roller applied, water based acrylic sealer for CONPELL Envirogrip

DESCRIPTION

Envirotop W is a water based, general purpose, semi-gloss acrylic sealer designed to make CONPELL Envirogrip easy to clean while ensuring the surface is resistant to penetration from oils and other liquids. Envirotop W should be applied to CONPELL Envirogrip as a one or two coat application.

PRODUCT FEATURES & BENEFITS

- Excellent adhesion with good hot tyre pickup resistance
- Easy to apply with spray or roller application
- Comes ready to use and is easy to re-coat
- Environmentally friendly, "Green star building code compliant".
- Good early water resistant
- Suitable for internal and external use
- Cost effective

TYPICAL APPLICATIONS

Envirotop W is designed as a clear semi-gloss /gloss top coat for the CONPELL Envirogrip textured finish.

APPLICATION RATES

Envirotop W is designed for a one or two coat application, total application rates are typically between 8m² per litre per coat depending on the the desired result. (Contact manufacturer for more details).

PACK SIZES

Envirotop W is available in 1000ltr, 200ltr & 15ltr containers.

PERFORMANCE PROPERTIES

COLOUR	CLEAR WHEN DRY
FINISH	SEMI GLOSS
VOLUME SOLIDS	APPROX 25%
SPECIFIC GRAVITY	APPROX 1.0 KG/LTR
POT LIFE	12 MONTHS IN FULLY SEALED DRUM
DRYING TIME	TOUCH DRY 30 MINUTES @ 25°C
RECOAT TIME	2-4 HOURS AT 25°C
FULL CURE	7 DAYS @ 25°C

Envirotop W

Spray or roller applied water based acrylic sealer for CONPELL Envirogrip

SURFACE PREPARATION

The CONPELL Envirogrip texture finish must be sufficiently cured that the applicator can stand on the surface while applying the Envirotop W sealer. The Envirogrip texture finish should be clean and dry and free of all contaminants prior to the application of the Envirotop W sealer.

Application

FIRST COAT

1. Apply Envirotop W using a low -pressure spray unit or brush and roller, apply an even coat at the recommended application rate.
2. Allow a minimum of two hours between coats,.

SECOND COAT (If required)

Stir thoroughly and apply as above, apply the second coat at right angles to the previous coat.

Envirotop W

Spray or roller applied, water based acrylic sealer for CONPELL Envirogrip

CLEAN UP

Wash all equipment thoroughly with water.

CURING

Curing time depends on the temperature. Envirotop W is usually touch-dry in 20 minutes at 25°C.

The concrete can usually be walked on after 24 hours. Allow seven days before using vehicular traffic or cleaning with chemicals.

PRECAUTIONS

- Do not apply to damp surfaces.
- Protect surrounding areas from over-spray, buildings, plants, drains etc.
- Wear suitable protective wear, protective clothing, safety goggles and organic vapour respirator.
- Protect sealed surface from moisture for a minimum of 3 -6 hours.
- Avoid applying Envirotop W in windy conditions.
- Apply Envirotop W between 10°C - 35°C. Do not apply above 75% humidity. **DO NOT APPLY ENVIROTOP W IF TEMPERATURES ARE BELOW 10° C.**

STORAGE

- Keep Envirotop W stored in a dry area, away from direct sunlight & frost.
- Store between 10°C & 30°C.
- Envirotop W has a shelf life of 12 months in an unopened container.
- Ensure partly used drums are correctly sealed.

FIRE

Envirotop W is non-flammable.

Dura Shield AW

Spray unit applied water based acrylic sealer for masonry surfaces

SAFETY PRECAUTIONS

- Wear appropriate protective equipment, including clothing, gloves, appropriate respiratory mask and goggles.
- If poisoning occurs, contact doctor or Poisons Information Centre.
- If contact with skin occurs, remove contaminated clothing and thoroughly wash skin.
- If swallowed do not induce vomiting, give a glass of water.
- If in eyes, hold eyes open and flood with water for at least 15 minutes then see doctor immediately.
- For further information refer to the relevant Material Safety Data Sheet.

IMPORTANT INFORMATION

The information and recommendations relating to Envirotop W are given based on current knowledge and experience. Due to variances in material substrates and site conditions no warranties implied by law or fit to purpose of the product can be implied. We accept no responsibility for loss or injury due to the incorrect handling or improper use of the product, limiting the cost of our liability to the replacement product cost only. Always refer to current Product Technical Data Sheets.

CONPELL

Head Office: PO Box 4252

Ph: 1300 966 118

Brisbane Sales: 0450 040 848

Loganholme DC, Qld 4129

Fax: 1300 922 001

National Sales: 0433 400 220

Email: info@conpell.com Web: www.conpell.com